



 **PROTEGE[®]**
Protégé Two Reader Standard Expander

Protégé Two Reader Standard Expander

The Protégé Two Reader Standard Expander module provides the interface of up to four reader inputs and 2 locking device outputs to the Protégé Integrated Access Control, Security and Building Automation system, an advanced technology security product providing seamless and powerful integration.

The Protégé Two Reader Standard Expander module provides interface with up to 4 reader inputs using industry standard card and reader protocols and controls dual monitored electronic locking device outputs.

Intelligent Reader Hardware Interface

The Protégé Two Reader Standard Expander provides extensive hardware advancements that provide flexible access control, area control and alarm monitoring:

- Connect two readers using the independent reader inputs or use the Two Reader operation to connect four readers providing dual entry and exit door connection.
- Provision to control up to three outputs per reader input with predefined configurations for instant connection (Red LED, Green LED and Buzzer Control).
- Support for intelligent reader tamper operation the system will monitor the reader for reader keep-alive transmissions using the programmed protocol.
- Data received display indicates a valid decode of the format on the DATA indicator and the reader number the information was received (Two Reader Mode).
- Individually fused and monitored reader power supply protected with auto reset electronic polythermal fuse and monitored reader supply voltage.
- Power output indicator shows power is available on the reader voltage outputs.
- Over 45 formats predefined for simple configuration, additional formats added using the format builder or implemented directly using the firmware update function.

Local Monitored Power Supply

The Protégé Two Reader Standard Expander operates from a 16VAC Input, utilizing low cost transformers and providing a fully monitored reader and door solution:

- Deep discharge prevention of the battery with automatic electronic cut-off.
- Manual or processor controlled battery charge selection of 350mA or 700mA.
- Intelligent charging algorithm monitors battery and AC supply allowing optimum performance to be achieved using standard lead acid batteries.
- Monitored signals for Battery Low/Disconnect and AC Failure using local trouble zones.

Arming/Disarming

The Protégé Two Reader Standard Expander module allows a user to Arm and Disarm an Area from a reader input when associated with a door:

- Deny access to a user based on the status of the area reducing false alarms.
- Dual presentation of the card can arm an area associated with the entry or exit direction of the door being accessed.
- Fail to arm programmable output can be programmed to provide feedback in the event areas fail to arm when using card reading functions.
- Prevent access to a keypad using a card and pin function or allow card presentation to automatically login the user at the associated keypad.
- Disarm an area associated with an elevator floor on access when using the Destination Reporting Interface in Elevator Mode.

Protégé Reader Expander Feature Set Comparison Chart

	Power Supply	Battery Backup	Aux PSU	Lock Outputs	Lock Monitoring	Reader Ports	Entry/Exit Readers	Zone Inputs	Isolated RS485 Ports	Non-Isolated RS485	Ethernet	Offline Users
PRT-RDM2	12VDC			2 Relay		2	•	6		1		10
PRT-RDS2	16VAC	•	1A	2 Electronic	•	2	•	8	1			10
PRT-RDI2	16VAC	•	1A	2 Electronic	•	2	•	8	2			2000
PRT-RDE2	16VAC	•	1A	2 Electronic	•	2	•	8	2		•	2000

Technical Specifications

Power	Operating Voltage Operating Current Auxiliary Output	15.5VAC to 16.5VAC, 50-60Hz, 40VA (Max) 119mA (207mA Max) 1.2A Fused / Monitored
Battery Backup	Type Charging Low Battery Electronic Disconnection	13.8V Sealed Lead Acid 350mA/700mA 11.2VDC Alarm, 12.5VDC Restore 8.76VDC
Cable Specifications	Protégé RS-485 Encrypted System Network Communication Protégé RS-485 Slave Network Communication	Beldon Part Code 9842 or Equivalent. CAT5 / 5e (up to a maximum length of 300m)
Communication	Serial Isolated Power Ethernet (Only on PRT-RDE2)	2 RS485 Isolated Communication Interface Ports 12VDC @ 28mA Optional 10/100Mbps Ethernet Communication Link
Readers	Standard Mode Multiplex-Reader Mode	2 Wiegand or Clock Data Readers providing one Entry/Exit door or two entry/exit only doors. 4 Wiegand Readers (connected in multiplex reader mode) providing any combination of entry or exit for two doors.
Zone (Inputs)	System Zones Enclosure Tamper	8 Standard zones individual resistor or no resistor per zone. Each zone links to programmable door function. Request to exit, Door contact, Bond sensing and request to enter. Normally Closed/Normally Open
PGM (Outputs)	Lock Control PGMs System PGMs	2 Fixed Voltage High Current Outputs (1.0A Continuous, 1.2A Max) Monitored with Auto Shutdown and Reportable Events. 6 50mA (Max) Open collector output for reader LED and beeper or general functions.
Temperature	Operating Storage Humidity	5° to 55°C (41° to 131°F) -10° to +85°C (14° to 185°F) 0%-85% (Non Condensing)
Dimensions	Height Width Depth Weight	183mm (7.20") 234mm (9.21") 35mm (1.37") 790gms (27.86 ounces)
The size of conductor used for the supply of all power to the Protégé Two Reader Standard Expander should be adequate in size to prevent voltage drop at the terminals of no more than 5% of the rated voltage.		

International Compliance Standards:

The Protégé Two Reader Standard Expander complies with the following international standards.

For an installation of the Protégé Two Reader Standard Expander to comply with any of the standards all installation procedures and programming configuration settings must be made in accordance with the required standard.

**Disclaimer:**

Whilst every effort has been made to ensure accuracy in the representation of this product, neither Integrated Control Technology Ltd or any employee of the company, shall be liable on any ground whatsoever to any party in respect of decision or actions they may make as a result of using this information. In accordance with the Integrated Control Technology policy of enhanced development, design and specifications are subject to change without notice.

Designed and manufactured by:

Integrated Control Technology Limited

Protégé® and the Protégé® Logo are registered trademarks of Integrated Control Technology Limited.

Copyright © Integrated Control Technology Limited 2003-2008. All rights reserved.

**Integrated Control Technology Limited**

Unit C, 6 Ascension Place, Mairangi Bay, Auckland, P.O. Box 302-340, North Harbour, Auckland, New Zealand

P +64 9 476 7124, F +64 9 476 7128

support@integratedcontroltechnology.com

www.integratedtechnology.com

Designers and manufacturers of integrated electronic access control, security and building automation products.